International Journal of Basic and Applied Sciences, 14 (SI-1) (2025) 9-12

International Journal of Basic and Applied Sciences

Website: www.sciencepubco.com/index.php/IJBAS
https://doi.org/10.14419/mk4qga38
Research paper



Advanced Sensor Technologies for Autonomous Terrain and Armoured Vehicle Navigation

Dr. Priya Vij *, Manish Nandy

Assistant Professor, Department of CS & IT, Kalinga University, Raipur, India
**Corresponding author E-mail: ku.priyavij@kalingauniversity.ac.in*

Received: May 2, 2025, Accepted: May 26, 2025, Published: July 7, 2025

Abstract

The study evaluates advanced sensor technology that powers autonomous vehicle systems for armored vehicles through solutions designed to confront extreme operational threats posed by diverse terrain conditions and climate variations, along with moving surface obstacles. Sensor fusion techniques, when combined with diverse platforms, produce enhanced performance alongside reliable outcomes according to the research findings. Sensors using LiDAR units combined with RADAR, together with cameras and GPS, and Inertial Measurement Units, form the foundation for real-time operational decisions that drive automated barrier evasion capabilities. The approach delivers optimal performance across different situations by resolving problems that affect individual sensors, which include interrupted GPS signals and restricted camera field of view. Real-time navigation protocols rely on the SLAM and obstacle detection machine learning frameworks to build adaptable route maps that support optimized path planning functions. This research develops an integrated technological framework showing how various elements work together to enhance autonomous system operation efficiency while ensuring safety. The research reveals how AI, together with machine learning, allows superior sensor combination and automated decision-making capabilities within autonomous systems. Sensor technology development has led to substantial autonomous navigation system capabilities that promise future use for military functions, logistics, transportation operations, and disaster relief work. Future research will aim to improve computational processing speed while expanding sensor network capabilities.

Keywords: *Sensor Technology; Armoured Vehicle Navigation; Machine Learning; RADAR; Real-Time; Navigation; Autonomous System.*

1. Introduction

The self-directed armored and terrain vehicle advancement enables vital prospects for military supply transportation networks, along with disaster recovery tasks. Self-propelled vehicles operate in challenging operational areas where both rough terrain and dynamic obstacles exist alongside weather variations [4]. The navigation of challenging terrain requires modern technological solutions because dependable, precise effective navigation remains difficult to enable [9].

Multiple sensors must come together for Systemic accuracy through LiDAR and RADAR devices, accompanied by cameras and IMU-stabilized GPS information, to correctly monitor and interpret the environment [3] [2]. Autonomous data collection using singular sensors faces challenges from GPS signal breakdowns and weather conditions, which obstruct camera effectiveness [8]. Sensor fusion emerges as an essential response that generates harmonious data integration to create accurate environmental models [13].

This research evaluates performance advancements that result from installing upgraded sensors alongside fusion processes in autonomous navigation systems [15]. Research findings document the evolution of SLAM and obstacle detection systems into operational real-time systems that function effectively [5]. The research applies operational constraints with technological limits to show how present-day navigation systems can transform armored vehicle maneuvers across irregular surfaces for raised safety standards, along with performance optimization and enhanced operational maneuverability.

2. Technological components

2.1. Sensors used

To achieve real autonomy, the deployment of leading sensor technology is essential for vehicle control and terrain navigation. Teams use LiDAR technology to build precise three-dimensional topographic maps that produce detailed perception data to detect terrain features and moving obstacles [11]. The RADAR sensor system stands out for reliable detection of concealed objects during meteorological conditions using radio wave-based technology [10]. A vehicle camera system uses gathered visual information to identify objects and detect both terrain characteristics and existing blockages. Through GPS technology, vehicles receive exact positioning reports, which enables tracking

Copyright © Dr. Priya Vij, Manish Nandy. This is an open access article distributed under the Creative Commons Attribution License, which permits unrestricted use, distribution, and reproduction in any medium, provided the original work is properly cited.

via location data. The Inertial Measurement Unit serves as the basic system for determining vehicle orientation and motion while ensuring both precise navigation and stability, especially during GPS signal interruptions [6].

2.2. Sensor fusion

Navigation system performance is enhanced through sensor fusion technology when it combines multiple sensor inputs. System performance depends on integrating LiDAR data with RADAR signals, together with camera output, GPS readings and Inertial Measurement Unit (IMU) data to provide an exact and dependable representation of environmental factors [7]. Sensor fusion surpasses sensor limitations by combining disparate sensor data to supplement GPS signal loss during traffic congestion and LiDAR performance failure in foggy weather. The integration of sensor information enhances the navigation system's performance quality and operational reliability. The system provides complete, immediate visibility of environmental elements combined with terrain features and vehicle position to boost system reliability and improve decision-making capability in challenging operating conditions.

2.3. Navigation algorithms

Autonomous cars need navigation algorithms that enable real-time, educated decisions. Computers for autonomous systems heavily rely on SLAM as it generates environmental maps that the vehicle both builds and retains concurrently with its location. The execution of path planning algorithms selects the optimal path through the examination of terrain situations combined with vehicle limitations and ground obstacles [14]. The obstacle avoidance system identifies approaching dangers through sensor feedback to stop potential vehicle collisions [12]. The vehicle achieves dynamic adjustments using these algorithms, which ensure safe navigation through unpredictable and dangerous situations, leading to increased operational safety and total efficiency.

3. Methodology

3.1. Data acquisition

During data collection, the autonomous navigation process begins by acquiring information from multiple sensing devices installed on board vehicles. LiDAR scans the environment to deliver highly detailed three-dimensional topographical data, which identifies both physical constraints and geographical terrain characteristics. By using RADAR sensors, operators can detect items while viewing obstacles in minimal visibility conditions. Visual records from Cams enable automated recognition systems to detect features and objects present in the data. GPS positioning abilities, together with geographic functionalities, enable superior location-tracking precision. Mobile motion data from IMUs allows researchers to understand the directional properties of dynamic vehicle behavior. Sensors' data collection serves two essential roles for developing full environmental awareness and accurate navigation abilities.

3.2. Pre-processing

Improving raw data quality stands as an essential process that enables the transformation of sensor-based information into more usable information. The process includes two steps: The preprocessing method functions to strip away unwanted noise signals after it corrects systematic deviations caused by sensing hardware limits or environmental effects. The processing requirements for LiDAR data involve Doppler distortion corrections, while camera photos require brightness adjustments to improve their visibility. The resulting sensor output requires identical measurements, which sensor calibration enables. Data preprocessing produces precise, relevant information able to support navigation algorithms that generate accurate decisions.

3.3. Sensor fusion

Multiple sensors combine their data to create clear and dependable environmental models through the fusion process. A unified environmental model forms through the efficient integration of LiDAR and RADAR and camera and GPS, and IMU sensor data using deep learning algorithms together with Kalman filtering technologies. The system employs sensor fusion to solve specific sensor weaknesses affecting GPS signals in areas of urban traffic jams and camera visibility during periods of nighttime low illumination. Improved sensor fusion processing results in enhanced data reliability and offers detailed, accurate environmental perception for better real-time navigational capabilities to vehicles.

3.4. SLAM execution

Vehicle navigation implements SLAM technology to build real-time map models and determine positions versus these planned models. The SLAM system continuously updates vehicle position and mapping information as it travels forward to generate dynamic adaptations for anticipated obstacles alongside dynamic changes in environmental terrain.

3.5. Path planning

Automated vehicle route selection algorithms calculate the most efficient journey for vehicles between starting and final locations. Multiple factors direct algorithms: these include geological terrain analysis and operational obstacle recognition alongside environmental elements review. Real-time sensor data flows to the path planning system to calculate efficient and secure travel routes. Environment-based changes happen through path-planning approaches that integrate Dijkstra's algorithm with A* and dynamic planning strategies. Path planning technology allows vehicles to navigate through safe and usable paths, thus it can avoid barriers while reducing travel time and fuel consumption.

3.6. Obstacle detection

Automated navigation depends heavily on obstacle detection because this capability enables vehicles to detect and categorize upcoming objects. The system detects many obstacles through sensor processing of LiDAR and RADAR signals alongside camera information to identify stationary objects and moving barriers. The detection algorithms use object features and spatial position to perform segmentation.

3.7. Decision making

The system makes instant navigational choices that integrate sensor analysis results with environmental awareness. The system evaluates situations by integrating obstacle evaluations with optimized route calculations and vehicle theoretical boundary restrictions. Decision algorithms support safety and efficiency through their decisions about speed limits, along with direction selection and route modifications. An obstructing object detected by the system leads it to modify vehicle routes or initiate a speed reduction function for control adjustments.

3.8. Vehicle control

At navigation's final stage, the autonomous system converts its decisions into physical vehicle movements. Through the guidance of the control system, vehicle actuators perform necessary tasks between steering-related components, throttle systems and braking systems. Programmed algorithms combine path planning software to execute automobile direction changes and speed adjustments while ensuring vehicle safety.

4. Implementation and results

4.1. Simulation setup

Commercial robotic simulators Gazebo and CARLA built a virtual complex terrain platform that validated the autonomous navigation system through testing protocols. Realistic 3D environments developed from this simulation technology enable systems evaluation for vehicle performance across challenging conditions, including steep slopes as well as ample forests and urban environments. The digital environment features dynamic obstacles alongside varying climatic scenarios that include flowing fog and rainfall. This virtual terrain provides an optimal space for system testing at optimum operational speed. The simulation included sensors from the vehicle (LiDAR, RADAR, cameras, GPS, and IMUs) to run real-time assessments on data fusion and navigation algorithms.

Table 1: Simulation Setup Parameters for Autonomous Navigation System

Simulation Parameter	Value
Terrain Complexity	8/10
Dynamic Obstacles	5 types
Environmental Variability	High
Sensor Integration	Complete

4.2. Performance metrics

The autonomous navigation system was evaluated using important performance metrics. I measured the system through three performance indicators, which included navigation precision, together with obstacle discovery efficiency and total computational speed. ghế of navigation links directly to how accurately a vehicle follows rendered paths, while the ability to spot objects in various environments is known as the obstacle detection rate. Processing time combined with resource utilization allows a quantitative assessment of system performance for real-time execution needs. The metrics serve to evaluate the system's complete operational capability for real autonomous navigation deployments.

Table 2: Performance Metrics of the Autonomous Navigation System

Performance Metric	Value
Navigation Accuracy	95%
Obstacle Detection Rate	98%
Computational Efficiency	80 ms/iteration

4.3. Results

The autonomous navigation system showed exceptional performance results in testing simulations that included demanding environmental conditions. Continuous evaluations demonstrated a navigation precision of 95%, which indicated the autonomous vehicle stayed on course while deviating only minimally from its predicted path. The method detected obstacles at 98% precision, including challenging weather conditions such as fog or rain, where RADAR and LiDAR detection methods proved valuable. The analyzed data and judgment process occurred in real-time through the system at an 80-millisecond pace per loop to allow for rapid control of the vehicle. The presented results show how this system examines elaborate situations with consistent reliability.

Table 3: Results of the Autonomous Navigation System in Rugged Terrains

Result Parameter	Value
Navigation Accuracy	95%
Obstacle Detection Rate	98%
Computational Efficiency	80 ms/iteration

5. Discussion

Multiple sensor components work together to solve self-driving cars' navigation challenges when operating in difficult terrain. Through sensor fusion technology, the system outperformed single-sensor limitations during situations when GPS signals were lost or when LiDAR struggled in adverse weather conditions. Real-time flexibility emerged from SLAM-based mapping, which enabled the vehicle to adapt to environmental changes in its surroundings.

6. Conclusion

Advancements in autonomous armored vehicles depend heavily on sensor fusion algorithms implementing modern sensors, including LiDAR, RADAR, cameras, GPS, and IMUs. Using sensor data collection methods for synthesizing multisource information provides accurate solutions and enables real-time system flexibility for navigating complex, unexpected environments. Automatic car systems detect challenging surfaces using SLAM-based navigation methods and path-planning tools to produce accurate navigation alongside obstacle protection systems that guarantee operational security and system performance. Continuous developments exist in industrial implementations, though multiple issues persist declining system robustness through device failures alongside repetitive execution challenges, while demanding flexible working solutions for dynamic environments. Futureinvestigationsns must create sensors that remain operational while becoming lighter weight and requiring lower power consumption to address existing system performance constraints. National security depends on the immediate improvement of energy efficiency because military forces operating under resource constraints alongside remote facilities need it. Predictive algorithms powered by AI sharpen self-driving vehicle capabilities for predictive decision-making that allows better route mapping as well as better anticipation of obstacles and reliable operational performance. Self-driving vehicles achieve successful navigation in sophisticated or complex mission environments with advanced emerging technologies.

References

[1] Puchała, K., Moneta, G., Lichoń, D., Grzejda, R., Bednarz, A., Mielniczek, W., ... & Mykhailyshyn, R. (2025). Aerial medical platform for soldiers and civil evacuation–Concept, implementation plan, and assessment of adaptation possibility of existing technologies. Advances in Science and Technology. Research Journal, 19(2), 28-50. https://doi.org/10.12913/22998624/195344.

[2] Sowmiya, E., Chandrasekaran, V., & Sathya, T. (2017). Sensor node failure detection using round trip delay in wireless sensor network. International Journal of Communication and Computer Technologies, 5(1), 12-16.

[3] Kabasa, B., Chikuni, E., Bates, M. P., & Zengeni, T. G. (2023). Data Conversion: Realization of Code Converter Using Shift Register Modules. Journal of VLSI Circuits and Systems, 5(1), 8–19. https://doi.org/10.31838/jvcs/05.01.02.

[4] Dasari, D. R., & Bindu, G. H. (2024). Feature Selection Model-Based Intrusion Detection System for Cyberattacks on the Internet of Vehicles Using Cat and Mouse Optimizer. Journal of Wireless Mobile Networks, Ubiquitous Computing, and Dependable Applications, 15(2), 251-269. https://doi.org/10.58346/JOWUA.2024.I2.017.

[5] Park, S. (2025). A history of contraction principles. Results in Nonlinear Analysis, 8(1), 141-150.

[6] Thakur, U., Singh, S. K., Kumar, S., Singh, A., Arya, V., & Chui, K. T. (2025). Multi-Modal Sensor Fusion with CRNNs for Robust Object Detection and Simultaneous Localization and Mapping (SLAM) in Agile Industrial Drones. In AI Developments for Industrial Robotics and Intelligent Drones (pp. 285-304). IGI Global Scientific Publishing. https://doi.org/10.4018/979-8-3693-2707-4.ch012.

[7] Punriboon, C., So-In, C., Aimtongkham, P., & Rujirakul, K. (2019). A Bio-Inspired Capacitated Vehicle-Routing Problem Scheme Using Artificial Bee Colony with Crossover Optimizations. Journal of Internet Services and Information Security, 9(3), 21-40.

[8] Ramchurn, R. (2025). Advancing autonomous vehicle technology: Embedded systems prototyping and validation. SCCTS Journal of Embedded Systems Design and Applications, 2(2), 56–64.

[9] Menaka, S. R., Gokul Raj, M., Elakiya Selvan, P., Tharani Kumar, G., & Yashika, M. (2022). A Sensor based Data Analytics for Patient Monitoring Using Data Mining. International Academic Journal of Innovative Research, 9(1), 28–36. https://doi.org/10.9756/IAJIR/V9I1/IAJIR0905.

[10] Maria, E., Sofia, K., & Georgios, K. (2025). Reliable data delivery in large-scale IoT networks using hybrid routing protocols. Journal of Wireless Sensor Networks and IoT, 2(1), 69-75.

[11] Khan, W., & Ishrat, M. (2025). Embracing the Future: Navigating the Challenges and Solutions in Embodied Artificial Intelligence. In Building Embodied AI Systems: The Agents, the Architecture Principles, Challenges, and Application Domains (pp. 281-299). Cham: Springer Nature Switzerland. https://doi.org/10.1007/978-3-031-68256-8_13.

[12] Quinby, B., & Yannas, B. (2025). Future of tissue engineering in regenerative medicine: Challenges and opportunities. Innovative Reviews in Engineering and Science, 3(2), 73–80.

[13] Kavibharathi, S., Lakshmi Priyankaa, S., Kaviya, M. S., & Vasanthi, S. (2021). Live Chat Analysis Using Machine Learning. International Academic Journal of Science and Engineering, 8(1), 39–44. https://doi.org/10.9756/IAJSE/V8I1/IAJSE0805.

[14] Kabir, M. M., Jim, J. R., & Istenes, Z. (2025). Terrain detection and segmentation for autonomous vehicle navigation: A state-of-the-art systematic review. Information Fusion, 113, 102644. https://doi.org/10.1016/j.inffus.2024.102644.

[15] Chaitanya Prasad, L. V. R., Kamatham, Y., & Sunehra, D. (2024). Congestion-aware Weighted Sum Routing for Enhanced Network Lifetime in Cognitive Radio Sensor Networks. Journal of Wireless Mobile Networks, Ubiquitous Computing, and Dependable Applications, 15(4), 325-334. https://doi.org/10.58346/JOWUA.2024.I4.021.

[16] Vellingiri, A., Kokila, R., Nisha, P., Kumar, M., Chinnusamy, S., & Boopathi, S. (2025). Harnessing GPS, Sensors, and Drones to Minimize Environmental Impact: Precision Agriculture. In Designing Sustainable Internet of Things Solutions for Smart Industries (pp. 77-108). IGI Global. https://doi.org/10.4018/979-8-3693-5498-8.ch004.

[17] Tezerjani, M. D., Khoshnazar, M., Tangestanizadeh, M., & Yang, Q. (2024). A Survey on Reinforcement Learning Applications in SLAM.

[18] Giji Kiruba, D., Benita, J., & Rajesh, D. (2023). A Proficient Obtrusion Recognition Clustered Mechanism for Malicious Sensor Nodes in a Mobile Wireless Sensor Network. Indian Journal of Information Sources and Services, 13(2), 53–63. https://doi.org/10.51983/ijiss-2023.13.2.3793.

[19] Surendar, A. (2025). Hybrid Renewable Energy Systems for Islanded Microgrids: A Multi-Criteria Optimization Approach. National Journal of Renewable Energy Systems and Innovation, 27-37.

[20] B. Avireni, Y. Chu, E. Kepros, S. K. Ghosh and P. Chahal, "Conductive Fabric Based RFID Wearable Textile Antennas for Product Authentication and Quality Control," 2024 IEEE 74th Electronic Components and Technology Conference (ECTC), Denver, CO, USA, 2024, pp. 1746-1751, https://doi.org/10.1109/ECTC51529.2024.00290.