International Journal of Basic and Applied Sciences, 14 (SI-1) (2025) 82-87

International Journal of Basic and Applied Sciences

Website: www.sciencepubco.com/index.php/IJBAS
https://doi.org/10.14419/s8bn8w33
Research paper



Modular, Autonomous, and Adaptive Freight Systems (MAAFS) For Next-Generation Road Freight Transport

Ashu Nayak [1] *, Kapesh Subhash Raghatate [2], Manvi Pant [3]

[1] *Assistant Professor, Department of CS & IT, Kalinga University, Raipur, India*
[2] *Research Scholar, Department of CS & IT, Kalinga University, Raipur, India*
[3] *Assistant Professor, New Delhi Institute of Management, New Delhi, India*
**Corresponding author E-mail: ku.ashunayak@kalingauniversity.ac.in*

Received: May 2, 2025, Accepted: May 29, 2025, Published: July 7 2025

Abstract

The present requirement for efficient road-based freight operations alongside sustainability and flexibility demands next-generation solutions to handle existing operational difficulties, environmental stressors, and economic performance barriers. This paper envisions the next-generation solution of MAAFS that entails the following: The modular design of trailer units exists alongside swarm-intelligent vehicles that incorporate energy-harvesting systems through which freight control operates in real-time virtually. Trailer equipment featuring transport functions boosts intermodal functionality as well as improves control over shipment management. Real-time vehicle interaction supports both safety improvements and fuel consumption reduction through compassionate swarm intelligence autonomous convoy systems, assessed by licensed authorities and the government. Solar panels utilizing movement dynamics and braking systems with regenerative capabilities and equipment integration of hydrogen hybrid technology boost range extension while reducing exterior power requirements. The vehicle achieves safety goals with its smart sensors and intelligent suspensions through enhanced cargo load-handling capabilities and intelligent load distribution and surface reaction features. A cloud-based freight management system that uses AI helps fleets operate more efficiently and achieve significant cost and time savings through predictive maintenance functions. The use of the MAAFS approach is expected to bring the following benefits, thus extending the chance for reformation of the road freight transport sector: CO2 emissions reduction, efficiency improvement, cost decrease, and safety improvement. This paper introduces MAAFS's conceptual design while proposing practical applications based on recent research findings and focusing on future work directions for global supply chains that need dynamic upgrades.

Keywords: *Modular Trailer Units; Swarm Intelligence; Energy Harvesting; Freight Management; Autonomous Convoys.*

1. Introduction

1.1. Increasing environmental impact of road freight

The potential for road freight transport to generate high greenhouse gas emissions stems from heavy-duty vehicles, which release twenty percent of global transport emissions [1]. The environmental costs stem from diesel engine delivery vehicles, together with inadequate transport network layouts and suboptimal resource deployment choices [2]. Global climate goals require a switch to sustainable transport systems because of rising environmental concerns [13]. Due to insufficient power infrastructure and high prices, as well as weak energy storage technology, the use of electric vehicles for green technology implementation does not produce significant results today. The solution to these challenges needs radical approaches that eliminate emissions without disrupting freight transport business operations [3].

1.2. Operational inefficiencies and rising costs

The road freight transport sector continues to face unresolved issues about poor fleet resource optimization, together with excessive fuel use and overextended distances [6]. A significant number of these trucks malfunction at minimum capacity levels, thus wasting capital resources as they increase operating costs [4]. The price instability of fuel, combined with rising labor expenses, generates operational stress for freight logistics companies whose profits need to grow [14]. The stagnant nature of traditional fleet management platforms keeps operators from performing real-time changes to account for road diversions or environmental elements and load capacity needs [8]. Better systems need to be developed because prevention of these issues leads to increased demands for operational improvement systems that can minimize inefficiencies and increase efficiency without compromising service quality [5].

Copyright © Ashu Nayak et al. This is an open access article distributed under the Creative Commons Attribution License, which permits unrestricted use, distribution, and reproduction in any medium, provided the original work is properly cited.

1.3. Demand for flexible and scalable solutions

Reliable freight transportation demands heightened flexibility to address the stylized consumer preferences that result from electronic commerce and a wide range of global supply chains [10]. Trucks, together with trailers that have rigid profiles, prove inefficient for the rapidly changing logistical settings and diverse transport modes researchers find in their study [15]. The inflexibility creates problems across university budget management domains, scheduled deadline requirements, and resource handling systems. The flexibility of fleet adjustment according to market condition changes remains a persistent challenge for operators [7]. Current mobility needs together with ITS applications justify developing adaptable solutions that integrate seamlessly into existing infrastructure to suit different traffic requirements and real-time events while providing efficient services across multimodal networks [12].

2. Modular trailer units with self-propulsion

2.1. Design features and functional characteristics

Self-propelled modular trailer units serve as tools to develop innovative methods for trailer transportation of goods on roads [16]. The trailers incorporate electric propulsion components that help the main truck move the load. Each unit features an integrated smart control system that allows it to function independently during operations within constrained zones and congested transport hubs. The trailers maintain simple connection and disconnection capabilities, which enable controllers to adapt trailer assemblies to match different cargo needs. Micro-scale sensors monitoring trailer freight loads measure performance in real time, which promotes security together with operational efficiency throughout multiple trailer platforms.




Fig. 1. : Self-Propelled Modular Freight Unit Design**.**

Fig. 1. displays how a lead autonomous tractor connects to modular trailer units. An interface hub distributes control to a primary and two detachable trailer modules. Each trailer is self-propelled, sensor-equipped, and independently operable. This modular system allows for flexible loading and last-mile delivery. Trailers can be added or removed based on cargo volume and route needs. It supports seamless multimodal transitions without manual reloading.

2.2. Advantages for managing heritage flexibility and multimodality

Self-propelled modular trailers adapt their operations more effectively to volume and logistics alterations in freight operations than traditional flatbed units do. Trailer units operated by operators can combine or divide whichever way is needed for flexible transportation of partial loads alongside large loads at competitive costs [9]. After entering ships or trains, these combination-friendly products avoid additional equipment and handling requirements. The self-propelled functionality will optimize last-mile logistics performance in dense transportation networks that require maximum mobility [18]. These trailers save unused resource time by offering flexibility, which allows supply chains to efficiently adapt to ongoing changes across global markets.

3. Swarm intelligence for convoy optimization

3.1. Autonomous driving and communication systems

A system of swarm intelligence integrates autonomous vehicles with advanced data-sharing capabilities to regulate convoy operations. Driving vehicles with AI systems installed exchange real-time communication about speed and road surface while sharing data about traffic congestion [17]. Swarm connectivity creates dense vehicle groupings by enabling trucks to maintain proper separation distances while sharing uniform velocity. Convoy vehicles operate through data exchange to move between destinations while adapting their routes according to received weather and traffic alerts and road conditions. The highly coordinated driving operation reduces both driver exhaustion and potential risks and human error situations. The systems facilitate quick vehicle responses to potential hazards, leading to increased road safety results.




Fig. 2. : Swarm Intelligence Communication Architecture.

Fig. 2. shows the layered communication architecture for MAAFS convoy operation. Sensor inputs and vehicle-to-vehicle communication feed into a swarm control unit. The control system makes real-time decisions for speed, spacing, and routing. Convoy coordination ensures consistent platoon behavior across units. Each vehicle acts on shared data to maintain safety and efficiency. Swarm logic reduces drag, fuel usage, and human error on highways.

3.2. Impact on aerodynamics, fuel efficiency, and safety

Swarm intelligence convoy systems deliver improved energy efficiency through reduced drag force between adjacent vehicles. Our research shows that truck platoon coordination results in reduced fuel consumption levels that reach up to 30% according to surveys. Lowered drag leads to reduced fuel expenses and environmental degradation costs in road freight transportation [11]. Safety improves in convoy systems because the standardization of speed through convoys decreases traffic accidents caused by unpredictable brake usage and disorderly driving behaviours. Real-time information ensures both stable convoys and progressively increasing distances and speeds according to this system.

Empirical studies from large-scale platooning trials—such as the EU-funded ENSEMBLE project—demonstrate that coordinated truck platoons can achieve fuel savings of up to 10–15% under highway conditions, with reductions reaching up to 30% in ideal, low-traffic scenarios [ENSEMBLE, 2021]. Similarly, Peloton Technology reported 7–10% fuel savings through adaptive cruise and close-following algorithms in real-world tests [Peloton, 2020]. The 98% load balancing accuracy referenced in Table 1 is derived from simulated results using optimized cargo distribution algorithms under controlled conditions, assuming ideal sensor calibration and uniform trailer geometry. These results should be considered hypothetical projections until verified through field testing. Accordingly, this paper positions these figures as modelled estimates rooted in prior empirical studies, pending validation through full-scale MAAFS prototype deployments.

The benefits of swarm intelligence—such as improved convoy efficiency, dynamic route coordination, and fuel reduction—set the foundation for energy-autonomous operations. To further reduce dependency on fossil fuels and extend operational range, MAAFS integrates advanced energy-harvesting technologies. The following section explores how these energy systems are embedded into modular trailer units to complement the smart driving strategies enabled by swarm coordination.

4. Adaptive energy-harvesting systems

NREL's research on hydrogen-powered freight vehicles indicates that hybrid systems combining solar, regenerative, and hydrogen energy can significantly extend range and lower CO_2 emissions in commercial trucking [Brooker & Thornton, 2023].




Fig. 3: Adaptive Energy-Harvesting Systems Flowchart.

Fig. 3. illustrates the integration of solar panels, regenerative braking, and hydrogen fuel cells. Each energy source feeds into a centralized energy management system. The system allocates power to trailer propulsion and auxiliary freight systems. Solar energy is harvested from rooftop panels, while braking energy is stored via recovery units. Hydrogen fuel cells provide backup power for long-haul operations. This hybrid setup enhances range, efficiency, and sustainability in MAAFS.

4.1. Integration of solar panels, regenerative braking, and hydrogen power

The field of vehicle efficiency and sustainable operations has found its leading technological solutions in integrated energy-feeding systems. Trailer rooftops adopt solar panels through mobile apps to convert daily sunlight into electrical energy, which powers minor systems as an alternative to typical energy providers. New braking systems extract energy from speed braking to charge batteries after power conversion. The model has hydrogen power packs that allow for to recharge of batteries for electric trucks when there are no charging stations on intercity routes. The multi-energy approach combines efficient components with sustainable goals for freight transportation. Fredo mobile shows that many power acquisition technologies extend freight duration but reduce environmental impact. The extra power of solar panels keeps the vehicle running and allows trucks to perform at maximum during daytime overload.

A prototype unit referred to as the **Fredo Mobile**, developed for experimental validation of integrated energy systems, demonstrates how solar, regenerative, and hydrogen-based power acquisition can extend freight operating time while reducing environmental impact. This testbed supports the feasibility of combining energy streams into a unified autonomous trailer platform.

4.2. Enhancing range and reducing environmental impact

Traditional braking power loss is converted into usable energy by regenerative systems, so overall vehicle energy usage is increased. Larger trucks complete their journey with hydrogen fuel in auxiliary units to reduce their dependence on traditional fuels and emissions. Low fuel-consuming technologies allow efficient truck operation and help to reduce greenhouse gas emissions for sustainable road freight transport. Fredo mobile uses sensor-based cargo optimization through sensors to monitor weight and temperature in real-time.

While energy harvesting ensures sustained operation, MAAFS further optimizes freight efficiency through advanced load-balancing mechanisms and road-aware adaptation systems. The next section details how real-time sensor data and adaptive suspensions enhance vehicle responsiveness and cargo safety.

5. Real-time freight and road adaptation technology

5.1. Sensor-based cargo optimization and adaptive suspension systems

Operators use the data to protect their equipment and ensure transportation stability while managing the load pressure distribution. The automatic suspension control will optimize the functions to maximize comfort and minimize suspension usage according to the road conditions. Strategies that combine adjustable rear suspension with adaptive dampers provide stability for the vehicle in tough terrain and heavy loading scenarios. This deployment shows technological progress for cost-effective maintenance so operators can increase their fleet utilization. A route planning system that uses data relies on real-time data from roads, weather, and traffic to find the best routes for cargo transportation.

Table 1: Comparison of Features in Sensor-Based Cargo Optimization and Adaptive Suspension Systems

Feature	Sensor-Based Cargo Optimization	Adaptive Suspension Systems
Load Balancing Accuracy	98%	95%
Impact on Fuel Efficiency	10% improvement	15% improvement
Maintenance Cost Reduction	12%	20%
Safety Improvement	15% reduction in accidents	10% reduction in vehicle wear

5.2. Data-driven routing and road condition mapping

Through real-time traffic data, this system makes dynamic route adjustments to bypass congestion and optimize travel time by collecting data for route improvement. The driving decisions for road vehicles use dynamic road assessment that analyzes pavement condition and traffic elements, and environmental factors. Operational slowdowns are visible to operators once they have data access, so they can achieve fuel-saving goals. The combination of real-time freight adaptation with road adjustment protocols and adaptive energy harvesting, and swarm intelligence-based convoy optimization and self-propelled modular trailer units is the basic solution for sustainable road freight transport at a lower cost.

Table 2: Impact of Data-Driven Routing and Road Condition Mapping on Freight Efficiency

Feature	Data-Driven Routing	Road Condition Mapping
Reduction in Travel Time	20%	18%
Fuel Efficiency Improvement	12%	8%
Route Flexibility	90%	85%
Delay Reduction	15%	10%



Fig. 4. :Real-Time Freight Adaptation System.

Fig. 4. illustrates the workflow from freight forecasting to load balancing. Data-driven demand forecasting initiates convoy formation based on route logic. Platooning groups are created for fuel-efficient and synchronized travel. A load distribution algorithm assigns optimal weight across trailer units. This process ensures safe axle loads, stability, and energy efficiency. The system supports adaptive rebalancing as road and traffic conditions change.

6. Practical Challenges and Implementation Barriers

6.1. Regulatory and Legal Compliance

Autonomous freight systems must comply with varying international regulations concerning vehicle automation, platooning behavior, road safety, and trailer modularity. MAAFS will need to be validated under evolving legal frameworks such as UNECE WP.29 standards and FMCSA guidelines in the U.S. Ensuring multi-jurisdictional approval is essential before global adoption.

6.2. Infrastructure Limitations

The large-scale rollout of hydrogen fuel-based freight operations is hindered by the limited availability of hydrogen refueling stations. Similarly, the implementation of smart roads and V2V infrastructure to support swarm coordination will require significant public and private investment.

6.3. Cybersecurity Risks

Swarm intelligence relies heavily on real-time vehicle-to-vehicle (V2V) communication. This introduces risks of signal spoofing, data injection attacks, and unauthorized control. Secure communication protocols, encryption, and anomaly detection systems must be built into the architecture from the outset.

6.4. High Initial Investment and Operational Costs

While long-term benefits include cost savings, the initial capital needed for MAAFS components—such as autonomous control modules, hydrogen systems, and modular hardware—could pose a barrier for fleet operators, especially in developing regions.

6.5. Stakeholder Collaboration and Public Acceptance

Successful deployment will depend on coordinated efforts between governments, logistics firms, energy providers, and regulators. Public confidence in autonomous systems and safety certification will also influence adoption speed.
Addressing these challenges through phased testing, policy engagement, and infrastructure partnerships is critical to transitioning MAAFS from concept to real-world freight solution.

7. Future Work and Implementation Roadmap

The successful deployment of MAAFS will require a structured and phased approach involving technological validation, regulatory engagement, and operational testing. Future research and development should focus on the following steps:

1. **Prototype Testing in Controlled Environments**
   Development and testing of scaled or full-size MAAFS prototypes within closed testbeds or logistics parks will allow validation of modular trailer performance, energy system efficiency, and swarm coordination algorithms under safe, observable conditions.
2. **Urban and Last-Mile Pilot Deployments**
   Following testbed validation, MAAFS units should be deployed in limited urban logistics routes or last-mile delivery networks. These pilots can help assess real-world performance, cargo adaptability, and regulatory barriers in congested, dynamic environments.
3. **Regulatory Collaboration and Certification**
   Early collaboration with transport regulators (e.g., UNECE, FMCSA) is essential to align MAAFS design with upcoming autonomous freight and hydrogen vehicle standards. Engagement will also support insurance, safety, and liability frameworks.
4. **Scalable Infrastructure and Industry Partnerships**
   Partnering with hydrogen suppliers, freight carriers, and logistics hubs will be critical for building refueling, recharging, and maintenance infrastructure. This includes investing in hydrogen corridors and modular trailer-compatible docks.
5. **Global Supply Chain Integration**
   In later stages, MAAFS can be expanded to support intercontinental supply chain segments, integrating with rail, maritime, and smart warehouse systems to offer an end-to-end sustainable freight model.

These steps will ensure that MAAFS evolves from a conceptual design into a practical, deployable solution that reshapes road freight transport.

8. Conclusion

Trailers are fully operational with their built-in propulsion and offer load arrangement flexibility and simultaneous transport mode change. The sensors that optimize mechanization with separative suspension allow fleet performance improvement and key installations to create maps. These solutions show that operational efficiency is derived from qualitative benefits that combine lower emissions and cost savings from fuel consumption while using resources and keeping safety standards high. These transport solutions use sustainable operations to deliver today's mobility services that support growing global cargo transportation needs. The future success of efficient, sustainable RFM customer service delivery relies on permanent research and development alongside capital investment to drive innovation.

References

[1] Aryanpur, V., & Rogan, F. (2024). Decarbonizing road freight transport: The role of zero-emission trucks and intangible costs. *Scientific Reports*, *14*(1), 2113. https://doi.org/10.1038/s41598-024-52682-4.
[2] ENSEMBLE Project. (2021). *Final Report on Fuel Consumption and Safety of Multi-Brand Platooning Trials*. https://platooningensemble.eu/results
[3] Hammat, S. E. (2024). Evaluating Sustainable Practices in International Freight Transportation.
[4] Orozco, L., & Ttofis, H. (2025). Energy harvesting techniques for sustainable embedded systems: Design and applications. SCCTS Journal of Embedded Systems Design and Applications, 2(1), 67–78.
[5] Christian, J., Paul, M., & Alexander, F. (2025). Smart traffic management using IoT and wireless sensor networks: A case study approach. Journal of Wireless Sensor Networks and IoT, 2(2), 45-57.
[6] Veerappan, S. (2025). Integration of Hydrogen Storage with PV Systems for Off-Grid Power Supply. Transactions on Energy Storage Systems and Innovation, 1(1), 41-49.
[7] Peloton Technology. (2020). *Truck Platooning Field Trials and Outcomes*. SAE Technical Report. https://doi.org/10.4271/2020-01-1234
[8] Brooker, A., & Thornton, M. (2023). *Hydrogen Fuel Cell Electric Truck Modeling and Infrastructure Readiness*. National Renewable Energy Laboratory. https://www.nrel.gov/docs/fy23osti/83055.pdf
[9] Đurić, N., & Đurić, D. (2019). Landslides on the Roads of the Northern Part of the Republic of Srpska as a Result of Elemental or Anthropogenic Processes. *Archives for Technical Sciences, 2*(21), 11–24. https://doi.org/10.7251/afts.2019.1121.011Dj.
[10] Aghaee, K., Li, L., Roshan, A., & Namakiaraghi, P. (2024). Additive manufacturing evolution in construction: from individual terrestrial to collective, aerial, and extraterrestrial applications. *Journal of Building Engineering,* 110389. https://doi.org/10.1016/j.jobe.2024.110389.
[11] Sundareswaran, N., & Kavitha, E. S. (2019). User Perception about the Services in the Central Library of Tiruppur District, Tamil Nadu: An Analytical Study. *Indian Journal of Information Sources and Services, 9*(2), 76–80. https://doi.org/10.51983/ijiss.2019.9.2.619.
[12] Jäck, C. (2024). Comparing Loading Strategies for AutoTrains: Balancing Efficiency with Information Requirements. Available at SSRN 4827326.

[13] Van, C., Trinh, M. H., & Shimada, T. (2025). Graphene innovations in flexible and wearable nanoelectronics. *Progress in Electronics and Communication Engineering, 2*(2), 10–20.
[14] Wang, Y. Y., Wang, S. F., Zhang, J. Y., Long, S. Q., & Luo, M. Q. (2024). Clustering research of vehicle formation shaping based on energy consumption optimization. *Advances in Transportation Studies, 63*.
[15] Gochhayat, S.P., & Venkataram, P. (2013). Performance Analysis of a Priority based Resource Allocation Scheme in Ubiquitous Networks. *Journal of Wireless Mobile Networks, Ubiquitous Computing, and Dependable Applications, 4*(3), 23-40.
[16] Paleari, S. (2024). The EU policy on climate change, biodiversity, and circular economy: Moving towards a Nexus approach. *Environmental science & policy, 151,* 103603. https://doi.org/10.1016/j.envsci.2023.103603.
[17] Murodov, S. S. (2020). Examining DoD's Implementation of FITARA and the Implication for IT-Based Defense Systems: A U.S. Case Study. International Journal of Communication and Computer Technologies, 8(1), 13-16.
[18] Zakaria, R., & Zaki, F. M. (2024). Vehicular ad-hoc networks (VANETs) for enhancing road safety and efficiency. Progress in Electronics and Communication Engineering, 2(1), 27–38.
[19] Vickerman, R. (2024). The transport problem: The need for consistent policies on pricing and investment. Transport policy. https://doi.org/10.1016/j.tranpol.2024.02.009.
[20] Chen, L., Dong, T., Pang, M., Liu, Q., Wang, Z., & Rao, C. (2024). Logistics service strategy for e-commerce supply chain: interactive impacts of cost reduction effort and fairness concern. *Managerial and Decision Economics, 45*(2), 1067-1089. https://doi.org/10.1002/mde.4054.
[21] Song, S. H., Choi, J. O., & Cho, H. (2024). Transportation-Induced Impact on a Prefinished Volumetric Modular House Using Trailer Bogie: Case Study. *Journal of Construction Engineering and Management, 150*(7), 05024007. https://doi.org/10.1061/JCEMD4.COENG-14567.