

CFD analysis for counter flow in concentric tube heat exchangers

Banoth Mohan^{1*}, V. Ashok Kumar²

¹Asst. Professor, School of Mechanical and Automotive Engineering, College of Engineering and Technology, Dilla University, Dilla.

²Associate Professor, HOD, Department of Mechanical, Mother Theresa College of Engineering & Technology, Peddapalli.

*Corresponding author E-mail: banothmohan2012@gmail.com

Abstract

A device may be a device worked for the sensible heat exchange beginning with one liquid then onto the attendant, paying very little reference to whether or not the liquids square measure isolates by a powerful divider in order that they ne'er mix, or the liquids square measure particularly in touch. reliably get some data concerning in device progression is creating to form productive, traditionalist and stinging heat exchangers, where for the duration of the planet. Strengthening the function for this alteration wants associate degree association. In most up-to-date 5 years coaxial tube heat exchangers use unnatural convection to cut down the temperature of a operating liquid whereas raising the temperature of the cooling medium. The motivation driving this paper is to utilize ANSYS FLUENT12.1 programming and hand counts to interrupt down the temperature drops as a neighborhood of each straight speed and delta temperature and the way each modification with the opposite. every gleam money dealer show was worked in steps and examined in transit till the purpose that the instant that each parallel stream and counter stream heat money dealer models were created. The outcomes were thought of between every model and among parallel and counter stream with fouled funneling. Turbulent stream was conjointly impecunious down amidst the distinction within the shine exchangers to choose its impact on heat exchange. whereas clearly the fouled heat money dealer had a lower execution and during this manner cooled the operating liquid less, the execution of the counter heat money dealer out of the blue of the parallel heat money dealer.

1. Introduction

Project background

The glow money handler may be a contrivance that changed the nice and cozy from hot medium to chilly medium while not amalgamated each of medium since the 2 mediums area unit isolated with a robust divider for the foremost half. There area unit different types of heat money handler that used as a neighborhood of purpose of read of the applying. For define, twofold pipe heat money handler is employed as a touch of development method like consolidating the vapor to the fluid. Right once to gather this type of heat money handler, the amount of fabric that require to utilizes should be thought of since it affected the final heat exchange constant. For this type of heat money handler, the outlet temperature for each hot and icy liquids that passed on is surveyed by utilizing the most effective style of this type of heat money handler.

Literature survey

The distinction in liquid stream and temperature profiles of a liquid within the wake of experiencing a fulminant amendment in divider temperature is dependent on the liquid properties and additionally the temperature of the divider. This heat passage issue is extraordinary because the Graetz drawback. From reference [1] for incompressible Newtonian liquid stream with unflinching ρ and k , The speed profile will in like approach be creating and may be used for any Prandtl variety material expecting the speed and temperature profiles area unit starting at a comparable purpose [2]. For the essential Graetz issue, Poiseuille stream was recognized

and condition was used to portray the utterly influenced speed to field of the liquid hunt through the anticipated divider temperature conduit. uninflected the paper from Sellars [3] wherever he becomes the Graetz issue, this condition for speed is just too used. For the motivations driving this paper and therefore the use of the compelled fragment program, a dependable helper for the gulf speed was used. This deduces a balanced Graetz issue was shown and isolated. within the cases thought of, gas was accepted to course through the inward pipe that was fabricated from copper and cooled by the external coaxial pipe during which water was spilling. Material properties, as an instance, dynamic thickness, thickness, Prandtl variety, and heat conduction were gotten from reference [4]. Graetz found a solution as an enormous arrangement during which the eigenvalues and breaking points consummated the Sturm-Liouville structure. whereas Graetz himself thus to speak picked the basic 2 terms, Sellars, Tribus, and Klein [5] may broaden the problem and choose the fundamental 10 eigenvalues in 1956. As a general rule paying very little relevancy the approach this more engineered up the key arrangement, at the phase of the conduit the course of action had to a extremely degree poor mix wherever up to 121 terms would Mnot have an effect on the blueprint to consolidate. Helmut Schmidt and Zeldin[6] in 1970 extended the Graetz issue to merge basic heat conductivity and located that for top Peclet numbers (Reynolds numberduplicated by the Prandtl number) the problem course of action is actually the principle Graetz issue. Hwang et al [7] surveyed weight drop {and heat[and heat} move constant in utterly influenced laminal pipe to stream utilizing continued warmth development conditions. In lightweight of the check happens they incontestable that the wildcat pounding variable was in wonderful synchronization with the theoretical appraisals utilizing the Darcy condition. Bianco et al [8] watched simply amaximum of St

Martin's Day capability among single and 2 stage happens for the laminal association. Akbari et al [9] astonishingly looked specific 2 stage models and therefore the single stage show within the laminal association. Single and 2 stage models apparently expected unclear fluid mechanics fields but whole completely different heat ones. The phrasing representational process the speed development in a very pipe stream crosswise over completed turbulent stream is settled and shown in Bejan, "Convective heat exchange coefficient",1994. Hydro powerfully created stream is refined in a very pipe once a selected length i.e. entrance length lupus erythematosus, wherever the impact of consistency goes to the purpose of merging of pipe. Directly the speed acknowledge many typical profile over the pipe that is no additional influenced by any edge impacts ascending out of the approach district. The surge of real liquids demonstrate thick impacts in pipe stream. Here this impact is perceived for turbulent stream conditions. A additional real take a goose in any respect the check and numerical works uncovers that by a large margin the bigger a part of the strained convective heat move considers in pipe stream are finished with determined divider development limit condition. thus during this work, a productive procedure liquid dynamic examination with continued divider temperature stipulation has been done obtaining a handle on the only stage approach within the turbulent association and therefore the outcomes area unit separated and therefore the symptomatic and numerical outcomes accessible within the composing.

2. Problem statement

The twofold pipe heat money handler is employed as a touch of business as an instance, condenser for {chemical method|chemicalchange|chemicalaction|naturalprocess|naturalaction|action|activity} and cooling liquid process. This twofold pipe heat money handler is created in a very liberal size for prodigious application in business. To have an effect on this small twofold pipe to heat money handler kind progress toward obtaining the prospect to be trait, the most effective game set up for this small twofold pipe heat money handler is choose. Heat exchange is taken into account as exchange of heat vitality from anatomy to a different. Heat exchange is that the most elementary parameter to be assessed because the execution and reasonability of the coaxal tube heat money handler. By utilizing CFD recreation programming, it can lessens the time and activity value dismembered by Diagnostic computations to examine the best parameter and therefore the lead of this type of heat money handler.

Objectives of research

The goal of this examination is to convey additional complete understanding Flow maldistribution in cannular heat money handler by taking a goose at space weighted and mass weighted temperature profiles formaldistribution while not pivot and maldistribution with switch. Moreover, association of common temperature profiles of stream maldistribution with the run of the mill temperature profiles of uniform mass stream development. This numerical examination was increased the circumstance the coaxal tube define with varied estimation of tubes. A restricted volume numerical course of action is employed to check the conjugate heat exchange and liquid stream qualities with the guide of the procedure swish motion (CFD) business code, FLUENT. The addressing conditions for the position and essentiality security were seen numerically with the uncertainty of three-dimensional set stream. a robust model, the standard based k-ε turbulence show was related in thisexamination. As diagrammatic within the space one.2, the open basic composed work is to a good degree restricted as for the deliberate additionally, it's thus far arduous to expect the fabric craft of the stream maldistribution within the winding tube banks. As wants be, temperature dispersals within

the package were pondered numerically. The target of this examination is to make up a CFD beguilement to anticipate heat Transfer in coaxal tube heat money handler by utilizing explicit fluids.

Scopes of research


The degrees of this examination area unit as per the going with:

- Spotlight on heat exchange for heat money dealer explicit to twofold pipe heat money dealer forms.
- style the twofold pipe heat money dealer by utilizing ANSYS work table.
- Reenactment in twofold pipe heat money dealer by utilizing FLUENT programming.
- Examination the gleam money dealer explicit to stream rate of hot and nipping liquid.
- To repeat heat move in homocentric tube heat money dealer by utilizing CFD-Fluent programming.
- To isolate the shine move in homocentric tube heat money dealer by wanting age result to the Analytical figurings. Bolster redirection results to the Analytical figurings within five-hitter botch.

Problem description and modelling

Geometry modelling

The geometry made in ANSYS workbench. This geometry imported to ansys well-known and repairs the geometry. The geometry involves a length of 1m. Concentric holder of interior tube internal separation crosswise over 0.1m and outer tube inside broadness 0.24m.



For this meander, fully influenced laminal and turbulent incompressible liquid to stream are going to be explored in 3 heat money changer cases: parallel stream, counter stream, and stream during a fouled heat money changer. the next temperature refinement are going to be looked be settled as a edge of the sound speed and delta temperatures. the overall target is to select the foremost extraordinary temperature capability in these cases for each laminal additionally, turbulent stream for a mixture of stream rates and delta temperatures. to switch the live of things, water and oil are going to be raised because the liquids to stay up viscosities and densities of the liquids solid. the kind of heat money changer utilised are going to be of coaxial tube define. Water are going to be the cooling medium and oil the operating fluid.

Shaping material properties

Water was utilised because the base liquid hunt through tube or coordinative. Its material properties were settled from tables in lightweight of the temperature that was being noncommissioned within the model. The fabric was depicted in acquainted utilizing its material program. For the extraordinary stream configuration issue show sure properties were delineated by the shopper going before choosing the model, these properties were: heat physical phenomenon, thickness, heat most distant purpose at unblinking weight, degree of specific warms, and dynamic consistency. For the balanced Graetz issue with pipe divider physical phenomenon and furthermore for the nice and cozy money changer models the fabric library properties in acquainted were used.

3. Simulation

Finite volume method

The mass, importance, and scalar transport conditions square measure inspired over all the liquid components in a very machine area utilizing CFD. The compelled volume framework could be a specific restricted differencing numerical technique, and is that the most while not a doubt appreciated strategy for computation stream in CFD codes. This phase portrays the main frameworks connected with duty-bound volume figurings. The confined volume framework fuses initial creating associate amusement arrangement of numerical conditions through the system of discretising the coordinating conditions for mass, power, and scalar transport. to deal with stream changes due to turbulence during this enterprise, the RANS conditions square measure discretised rather once the cases square measure run utilizing the k-epsilon turbulence seem. exactly once the conditions are discretised utilizing the smart differencing arrange for bestowing the differential articulations within the basic condition (i.e. focal, upwind, mixture, or power-law, or alternative higherorder differencing plans), the following power conditions square measure unraveled at every put concentration of every cell.

Numerical framework and machine approach


The addressing differential transport conditions were modified over to power conditions antecedently being grasped numerically. once the affirmation of the aim of imprisonment condition, the strategy management and also the introduction of the game-plan should run before the stress begins. The arrangement controls just like the weight speed coupling and also the disconnection of the novel factors and also the cathartic up factors should be settled. The courses of action dynamic estimation (called the withdrew thinker) utilised as a touch of the numerical tally needs less memory that the coupled solver. Since we have a tendency to square measure utilizing the separated thinker for our stress, the default underneath cathartic up factors square measure utilised and also the easy game arrange for the load speed coupling is used and

also the second separation is used for the facility and also the commonplace game arrange is used for the load.


4. Result and discussions

The impression of CFD redirection happens of course square measure examined beneath on the far side what several would think about potential conditions. to choose the simplest game arrange for twofold pipe heat money changer kind.

- Results are going to be desperate down utilizing ANSYS acquainted.
- Hand figurings are going to be done to use as a cross check
- ANSYS FLUENT could be a useful mechanical gathering to exhibit laminal stream warm trade.



Cooling water velocity vs. the outlet temperature of different fluids for copper tube material



Cooling water velocity vs. the outlet temperature of different fluids for aluminium tube material

5. Conclusion

The execution, CFD examination of varied liquids in like manner, putting funnel materials were reviewed on parallel and counter stream in coaxial tube heat money dealer. The consummations of this investigation at ar as takes once.

- The fundamental focal point of this undertaking was to investigate the liquid stream in twofold pipe warm exchangers and the accompanying execution of these sparkle exchangers.

- To empower this examination, the ANSYS acquainted twelve.1 confined volume examination program was utilised to play out the airing and computations. Recollecting a definitive goal to visualize the movement of every model, the models were worked piecemeal and every stage assessed and checked.
 - The imperative mastermind was a changed Graetz issue indicate where speed and temperature profiles were broke down for liquid stream in a compartment of 1.0 m long. This real model was certified by hand figurings and therefore the p.c capability plain was below two hundredth.
 - It ought to be seen, that for the lower speed of .0001 m/s, the bedded model very cooled the outlet stream to 305.148 K within the balanced Graetz issue whereas the turbulent show simply cooled the stream to 322.25503 K. it had been was} likewise found that the centreline temperature absolutely (0 to one m) had a lot of representative, back review transfer aloof from the cove temperature of 323.15 K to 305.93648 K whereas the turbulent stream had a for the foremost half straight association with the centreline temperature against the spherical piece length.
 - The parallel and counter stream models at first were certified to give a similar cooling relationship clearly from these sorts of warm exchangers. All models with and while not fouling incontestible that because the cooling water stream broadened, thus did the live of heat exchange by a decreasing oil outlet temperature and developing oil temperature separate.
 - The ANSYS FLUENT outcomes were seen to be extremely tried and true with hand estimations with the greater part of the attributes inside 5% of each other.
 - The material properties which were temperature subordinate were seen as unfaltering in light of the delta temperature of the liquid stream for the hand figurings rather than utilizing the commonplace temperature however the ANSYS FLUENT respects were from the material library.
 - The fouled warmth exchangers execution was much lower than the non-fouled warmth exchanger. There was a traditional two K rise in outlet temperature for a fouled coincidental heat amendmentr|moneyhandler|money dealer} and a traditional one K move in outlet temperature for a fouled countercurrent heat money dealer stunning affinity a bit live of a Kelvin change between the synchronous and countercurrent heat exchangers.
 - This discovering indicates it is more fundamental for fashioners and authorities to rotate around the methodology for retribution naughtiness to the gleam exchange surfaces and the sort of material picked than it is to base on the sort of stream. the extra time that's spent interested in however a fabric can perform once it slow and therefore the form of crumbling that happens with the fabric or approaches to manage expect usage and weakening within the structure are going to be a lot of profitable.
- [6] Subramanian SR, "The Graetz Problem", *Web.*, (2012).
- [7] Hwang KS, Jang SK & Chio SUS, "Flow and convective heat transfer characteristics of water-based Al_2O_3 nanofluids in fully developed laminar flow regime", *International Journal of Heat and Mass Transfer*, Vol.52, (2009), pp.193-199.
- [8] Bianco V, Chiacchio F, Manca O & Nardini S, "Numerical investigation of nanofluids forced convection in circular tubes", *Applied Thermal Engineering*, Vol.29, (2009), pp.3632-3642.
- [9] Akbari M, Galanis N & Behzadmehr A, "Comparative analysis of single and two-phase models for CFD studies of nanofluid heat transfer", *International Journal of Thermal Sciences*, Vol.50, (2011), pp.1343-1354.
- [10] Valko PP, "Solution of the Graetz-Brinkman Problem with the Laplace Transform Galerkin Method", *International Journal of Heat and Mass Transfer*, Vol.48, (2005).
- [11] Blackwell BF, "Numerical Results for the Solution of the Graetz Problem for a Bingham Plastic in Laminar Tube Flow with Constant Wall Temperature", *Sandia Report*, 1984.
- [12] White FM, *Fluid Mechanics, 3rd edition*. Mc-Graw Hill, (1994).

References

- [1] Concentric tube heat exchanger: operating principle with parallel flow, Art.
- [2] White F, *Viscous Fluid Flow*, 3rd ed. New York: The McGraw-Hill Companies, Inc., (2006).
- [3] Conley N, Lawal A & Mujumdar AS, "An assessment of the accuracy of numerical solutions to the Graetz problem", *International communications in heat and mass transfer*, Vol.12, No.2, (1985), pp.209-218.
- [4] Kays WM, Crawford ME & Weigand B, *Convective heat and mass transfer*, 4th ed. New York: The McGraw-Hill Companies, Inc., (2005).
- [5] Sellars J, Tribus M & Klein J, "Heat Transfer to Laminar Flow in a Round Tube or Flat Conduit-The Graetz Problem Extended", *The American Society of Mechanical Engineers*, (1955).