



# Adaptive modulation approaches parameters effect on LTE uplink waveform

Haider D. Aljanabi <sup>1\*</sup>, Bashar B. Qas Elias <sup>1</sup>, Hussam D. Aljanabi <sup>2</sup>

<sup>1</sup> Al Nisour University College, Department of Computer Engineering Techniques, Iraq

<sup>2</sup> Al-Mustafa University College, Department of Computer Engineering Techniques, Iraq

\*Corresponding author E-mail: [haider.th.eng@nuc.edu.iq](mailto:haider.th.eng@nuc.edu.iq)

## Abstract

The next generation are regarding radio applied sciences designed in conformity with increase the capability and velocity about cellular networks. LTE is the first science designed bluntly because the Next Generation Network NGN yet is embarking in conformity with come to be the de-facto (NGN) mobile get entry to network standards. It takes competencies of (NGN's) services in imitation of grant an always-on cellular information ride same after wired networks. In this paper LTE uplink waveforms displayed with various duplexing mode, Allocated Resources Blocks ARB, Modulation types and total information per frame, QPSK and 16 QAM used as modulation techniques and tested under AWGN and Rayleigh channels, similarity and interference of the generated waveforms tested using auto-correlation and cross-correlation respectively.

**Keywords:** LTE; Uplink Channel; NGN; ARB; AWGN.

## 1. Introduction

To give various administrations to client, administrators have assembled different systems, for example, settled phone systems, digital TV systems, cell phone and information systems. To outfit in excess of one application in congruity with client, administrators bear created in excess of one systems such so consistent cell phone systems, rope TV systems, cell phone systems or data systems. The Next Generation Network (NGN) introduces entire of this capacity the utilization of a plane all-IP inside that interconnects various access connected sciences at that point gives a steady and solid client encounter notwithstanding concerning the get passage to technique. The NGN base decision supply (QoS) bolster yet an immense assortment of highlights or administrations. The (NGN) get right of section to network will give dynamism and steering organization yet learn so the base sees the phone arranges basically to be specific another IP arrange. Versatile handover of get right of section to composes aim lie consistent as much the IP get admission to network controls security, confirmation, and charging for the numerous entrance advancements. The LTE is the 1st innovation's outlined expressly for the (NGN) and is set to end up the de-facto (NGN) mobile get to arrange standard. It takes potential about the NGN's capacities as indicated by give a dependably on cell information trip same as per wired systems [1], [2].

Permanency LTE supports height data rates about on after one hundred Mbps over the downlink then fifty Mbps about the uplink when the use of a twenty MHz race bandwidth, a individual dispose antenna at the user equipment (UE), then twain get hold of antennas at the Base Station. LTE produces ternary after 2 examples the throughput of the downlink yet two as per 3 times the throughput in regards to the Uplink companion to 3GPP Release 6. The LTE framework enhances range effectiveness, also depicted brother as per Release 6. The downlink target is 3 in similarity

with 4 examples the otherworldly effectivity in regards to High-Speed Downlink Packet Access (HSDPA) whilst the uplink target is a twain as indicated by three-time change upon High-Speed Uplink Packet Access (HSDPA) [3], [4]. LTE has adaptable duplex techniques. Both Frequency Division Duplex (FDD) yet Time Division Duplex (TDD) are genuine range allotments yet empower LTE as per concur various channel transmission capacities inside the accessible range [5], [6].

In this paper LTE uplink waveforms displayed with various duplexing mode, Allocated Resources Blocks ARB, Modulation types and total information per frame, QPSK and 16 QAM used as modulation techniques and tested under AWGN and Rayleigh channels, similarity and interference of the generated waveforms tested using auto-correlation and cross-correlation respectively.

## 2. LTE uplink transmission

The LTE framework does now not exclusively need more extensive transfer speed anyway likewise a more prominent better adjustment strategy than coordinating the high records statements of LTE transmission. OFDM is considered in congruity with lie the best tweak approach after play out the necessity of downlink transmission, the over the top (PAPR) statement of faith in regards to OFDM makes such significantly less well-disposed in light of the fact that the uplink transmission. Rather, the SC-FDMA strategy is unending a direct result of LTE uplink transmission [7]. the vital abilities concerning the utilization of SC-FDMA as a substitute with respect to OFDMA between LTE Uplink Transmission outline is the LTE uplink is suppositional after supply on in impersonation of 86 Mbit/s records rate. To pick up this, a cutting edge numerous entrance system should remain utilized. OFDMA be capable concede out and out high transfer speed however such furthermore creates intemperate (PAPR). Since between

cell terminals we use batteries there need to remain condition cordial uplink transmission. SC-FDMA is an answer in congruity with overcome the high (PAPR) problem. SC-FDMA has a lower PAPR which implies as it decision now not eat up as significantly control, philanthropy a more extended battery ways of life to the individual terminal [8], [9].

Likewise, as indicated by the low-PAPR ('single-bearer' property) common in SC-FDMA, such also has half wretched favored houses for a transmission plot. SC-FDMA permits in light of the fact that the open door as a result of low-multifaceted nature yet phenomenal adjustment between the recurrence space yet it is moreover practical after hold bendy transfer speed assignments along SC-FDMA. [10] Another advantage about SC-FDMA is the supposed "inherent" recurrence assorted variety. Since SC-FDMA go the information on some picture through whole the convenient subcarriers, subsequently into suit Fig. 1. Examination among OFDMA and SC-FDMA dropping a few records on certain (or additionally more) subcarriers fitting as per terrible blurring does now not generally prompt dropping the information tweaked inside the image. [8-10]




Fig. 1: Comparison into OFDMA or SC-FDMA.

The main components/elements of LTE that discussed in this paper are:

- Duplexing mode.
- Resources Blocks.
- Modulation types.

LTE bolster every Frequency-yet Time-Division-Duplex (FDD, TDD), which intends to that sum in FDD remarkable recurrence shackles are old in light of the fact that the downlink then uplink while among TDD downlink then uplink transmissions uses the indistinguishable recurrence band however are done in isolated schedule vacancies [5,6].

Two casing composes are characterized in light of LTE: Type 1, utilized into Frequency Division Duplexing (FDD) as demonstrated among Fig. 2.




Fig. 2: The Type1 Frame Type. Timing & Symbol Allocations Proven For FDD with Normal Cyclic Prefix.

Type 2, utilize TDD as much appeared of Fig.3 Type 1 outlines comprise in regards to 20 openings including spoor term with respect to 0.5ms. Sort 2 outlines incorporate two half casings. Depending about the switch time frame, at any rate some about the half casings incorporates a unique sub-outline conveying three fields in regards to change data: Downlink Pilot Time Slot (DwPTS), Guard Period (GP) and Uplink Pilot Time Slot (UpPTS). On the off chance that the switch period is 10ms, the change data happens just between sub-outline one. In the event that the swap period is 5ms, the switch information happens between every half casing, first into sub-outline one, once more in sub-outline six. Subframes zero yet 5 and DwPTS are constantly held in view of downlink transmission. UpPTS yet the sub-outline immediately agreeing UpPTS are saved on account of uplink transmission. Other sub-edges might be the uplink or downlink.

One over the basic advantages over the utilization of LTE-TDD frameworks is the ability as per powerfully exchange transfer speed in light of uplink or downlink, depending of present day needs, organize stack and so on sturdiness.




Fig. 3: Type 2 Body Type. Special Fields are Shown of Sub-Frames 1 and 6. Guard Duration Separates the Downlink and Uplink. This TDD Example Represents A 5ms Swap Point. A 10ms Swap Factor Would Now Not Bear the Distinct Fields in Sub-Frame 6.

### 3. The LTE resource block

In the LTE innovation, the time and recurrence assets of the accessible transfer speed are partitioned into littler squares to help enhance by and large framework proficiency and multi-client design. The data transfer capacity is vindicated inside wide assortment concerning symmetrical frequencies with a space of  $DF=15$  KHz known as subcarriers [12]. This subcarrier space 15 KHz helps holding Inter Carrier Interference as per the reduction organize likewise the cell client is moving with unnecessary speed and dispensing extreme Doppler movements of the recurrence.

A resource block (RB) or sub-outline framed a length 1ms utilizing 12 subcarriers and 12 or 14 OFDM images (contingent upon the length of (CP). Besides, the RB is subdivided of two spaces on 0.5ms each containing 6 or 7 OFDM images upon 12 subcarriers. Such awesome granularity over the time and recurrence assets causes arrange as indicated by particular exuberant clients all the while depending on the pipe requirements yet shameful components. These developing squares are gathered together in similarity with structure the radio assets [13-17].

In SC-FDMA showed in the fig. 4, the experiences is mapped into sign wonderful body consistent with the (QPSK; 16-QAM; or 64-QAM) balance, contingent on the channel conditions likeness to OFDMA. while, the QPSK/QAM pictures don't immediately change subcarriers; those pictures avoid through the serial to parallel converter joined by techniques for a DFT block that make discrete repeat region addressed of the QPSK/QAM pictures. beat framing is seen by DFT detail, anyway it's far non-obligatory and once in a while needs to shape the caution sign from DFT. if heartbeat framing is excited then in the bona fide signal, information transmission development occurs. The discrete Fourier pictures from the yield of DFT square are mapped with the subcarriers in subcarrier mapping square. Ensuing to mapping the repeat zone; the balanced subcarriers evade by methods for IDFT for time an area change. The loosening up of transmitter movement is for all intents and purposes indistinguishable as OFDMA [9], [16].




Fig. 4: SC-FDMA System. Block Diagram.

### 4. Simulation result

After implementing LTE uplink in MATLAB programing language, the proposed system testes under FDD and TDD duplexing mode, multi rate of resources Blocks, modulation type used of

QPSK and 16 QAM leading of various number of information per frame as follows:

- a) Duplex mode Frequency Division Duplex (FDD), QPSK modulation type, allocated resource blocks 6,15,25, total information per frame 6000,15440, 22160 bits respectively.

From Fig. 5 as number of resources block increased the bandwidth increased so the total information per frame increased.




Fig. 5: LTE Uplink RMC Wave Form with QPSK Modulation and FDD Duplex Mode, A- RB 6, B- RB 15, C- RB 25.

- b) Duplex mode Frequency Division Duplex (FDD), 16 QAM modulation type, allocated resource blocks 3, 15, 25, total information per frame 23440, 59920, 99120 bits respectively. With FDD duplexing mode and 16 QAM the results shoes same increasing parentage in bandwidth as RB increased with using QPSK modulation as shown in Fig. 6, total information per frame will increased with 16 QAM modulations.




Fig. 6: LTE Uplink RMC Wave Form with 16 QAM Modulations and FDD Duplex Mode, A- RB 6, B- RB 15, C- RB 25.

- c) Duplex mode Frequency Division Duplex (TDD), QPSK modulation type, allocated resource blocks 6, 15, 25, total information per frame 2400, 6177, 8464 bits respectively.




Fig. 7: LTE Uplink RMC Wave Form with QPSK Modulation and TDD Duplex Mode, A- RB 6, B- RB 15, C- RB 25.

With TDD duplexing mode of Fig. 7 if there is comparison with Fig. 5, the results shoes same percentage in bandwidth increasing as ARB increased but number of total information per frame will decreased to 2400,6177, 8464 respectively with TDD wile with FDD 6000,15440, 22160 as number of AEB increased.

- d) Duplex mode Frequency Division Duplex (TDD), 16 QAM modulation type, allocated resource blocks 3, 15, 25, total information per frame 9376, 23968, 39648 bits respectively.




Fig. 8: LTE Uplink RMC Wave Form with 16 QAM Modulation and TDD Duplex Mode, A- RB 6, B- RB 15, C- RB 25.

With TDD duplexing mode of Fig. 8 as compared with Fig. 7, 16 QAM increased number of total information per frame over QPSK, while comparison with Fig. 6, FDD mod increases number of total information per frame over TDD as number ARB increased in addition to bandwidth that increased with QPSK, 16 QAM, FDD and TDD as ARB increased.

- e) Testing Under AWGN and Rayleigh Channels: QPSK and 16 QAM tested under AWGN channel from Fig. 9 the results show butter BER performance with QPSK under AWGN channel with gain 4 dB of Eb/No in 10-8 BER while under Rayleigh channel the gain in Eb/No is 3 dB at 10-3 BER with QPSK modulation




Fig. 9: QPSK And 16 QAM under AWGN and Rayleigh Fading Channel.

f) Similarity test  
 LTE uplink with QPSK and 16 QAM waveforms examined using autocorrelation function in order to test the similarity of the wave forms, Fig.s 10 and 11 show the autocorrelation function of LTE uplink with QPSK and 16 QAM respectively with 6, 15, 25 allocated resources blocks, the results shows as number of allocated resources blocks increase the similarity decreased and the signal reaches the inequality.




Fig. 10: Autocorrelation Test of LTE Uplink Waveform with QPSK Modulation Using Various Allocated Resources Blocks AEB.




Fig. 11: Autocorrelation Test of LTE Uplink Waveform with 16 QAM Modulations Using Various ARB.

g) Crosstalk test  
 LTE uplink with QPSK and 16 QAM tested with cross correlation function in order to test the crosstalk or interference between sig-

nals as illustrated in Fig. 12, from the results the cross-correlation test shows better performance as number of allocated resources block increased.




Fig. 12: Cross Correlation Test of LTE Uplink Waveform between 16 QAM and QPSK Modulation Using Various ARB.

### 5. Conclusion

In this paper, LTE system uplink propose for the coming age of radio innovations and intended to build the limit, throughput, and speed of transmit information in the versatile systems, where Duplexing mode, Resources Blocks, Modulation types of the LTE uplink is the parameters that effect on the practical results, LTE has flexible duplex methods. Both (FDD) and (TDD)are legitimate range designations and enable LTE to oblige different direct data transfer capacities in the accessible range. In LTE, the time and recurrence assets of the accessible transmission capacity are isolated into littler squares to help multiuser and enhance by and large framework productivity, as number of resources block increased the band width increased so the total information per frame increased, QPSK and 16 QAM modulation approaches used in the LTE uplink and tested under AWGN, Rayleigh channels from the results QPSK shows better performance in term of BER with gain 4 dB and 3 dB in the tested channel respectively, similarity and crosstalk interference examined using auto-correlation and cross-correlation respectively, as number of ARB increased the performance of LTE uplink wave form is improved. Finally, the results of the parameters that examined in this paper which are Duplexing mode, Resources Blocks, Modulation types in the LTE uplink prove that the proposed system is the next generation of radio technologies.

### References

- [1] G. Vijayalakshmy, G. Sivaradje, " Interworking of WLAN-LTE for next generation wireless networks", Information Communication and Embedded Systems (ICICES), 2014 International Conference, IEEE, 09 February 2015. <https://doi.org/10.1109/ICICES.2014.7034085>.
- [2] Sajal K. Das, : "Mobile Terminal Receiver Design: LTE and LTE-Advanced", John Wiley & Sons , April 2016.
- [3] Sidak, Gregory (2016). "What Aggregate Royalty Do Manufacturers of Mobile Phones Pay to License Standard-Essential Patents" (PDF). The Criterion Journal on Innovation. Retrieved January 19, 2017.
- [4] Galetovic, Alexander; Haber, Stephen; Zaretski, Lew , "A New Dataset on Mobile Phone Patent License Royalties". Stanford University: Hoover Institution. Retrieved January 23, 2017.
- [5] Dan Jones (16 October 2012). "Defining 4G: What the Heck Is LTE TDD?". Light Reading. Retrieved 9 January 2014.
- [6] Ian Poole. "LTE-FDD, TDD, TD-LTE Duplex Schemes". Radio-electronics.com. Retrieved 9 January 2014.

- [7] Hikmei Sari Cristina Ciochina. "A review of ofdma and single-carrier fdma and some recent results. Advances in Electronics and Telecommunications", 1(1), April 2010.
- [8] T. Hong, "OFDM and its wireless applications: A survey", IEEE transactions on Vehicular Technology, Vol. 58, Issue 4, pp. 1673-1694, May 2009.
- [9] Guowang Miao, Jens Zander, Ki Won Sung, and Ben Slimane, "Fundamentals of Mobile Data Networks", Cambridge University Press, 2016. <https://doi.org/10.1017/CBO9781316534298>.
- [10] G. Sergiy Results of development of model for bandwidth management in LTE downlink with Resource Allocation Type 1 G Sergiy, ADAM Khodayer, AJH Dheyaa // The Experience of Designing and Application of CAD, 2015
- [11] Sujeet Kumar Jha, Rupa Rokaya, Amit Bhagat," LTE Network: Coverage and Capacity Planning", Networking and Network Applications (NaNA), 2017 International Conference, IEEE, 08 January 2018.
- [12] Chen, Qunhui (September 2011). "Evolution and Deployment of VoLTE" (PDF). *Huawei Communicate Magazine* (61). Archived from the original (PDF) on 2011-11-08.
- [13] V.A. Loshakov, H.D. Janabi, H.K. Al-Zayadi, "Adaptive control signal parameters in lte technology with MIMO", *Journal Telecommunications Problems*, vol. 7, no. 2, 2012.
- [14] Loshakov V.A. Improving Energy Consumption in Wireless Sensor Networks by LTE with MIMO / V.A. Loshakov, H.D. Al-Janabi, Y.T. Hussein // CADSM, 2013, 19-23 February, 2013, Polana-Svalyava (Zakarpatya), UKRAINE. P.226 – 230.
- [15] Al-Janabi, H.D. Using LTE technology in wireless sensor networks / H.D. Al-Janabi, Y.T. Hussein. // Radio: All-Round. international scientific-tech. issu – 2013. – vol. 172. – p. 81 – 88.
- [16] Loshakov V. A. Adaptive modulation in LTE technology by using OFDMA and SCFDMA with MIMO / V. A. Loshakov, H.D. Al-Janabi, Y. T. Hussein, N. T. Nasif // East European Journal of Advanced Technology (ISSN 1729-3774). – 2013. – Vol. 2/9 (62). – 8. – 11 p
- [17] Loshakov V. A. Adaptive spatial signal processing in LTE systems with MIMO / V.A. Loshakov, V.G. Likhogray, H. D. Al-Janabi, N. T. Nasif // KhPI №11, 2013. - P. 100–107.
- [18] Lemeshko OV, Al-Janabi Haider D, Al-Janabi Hussam D; Research of impact downlink parameters and service discipline on balancing process the subchannels number allocated to subscriber stations in WiMAX. Radiotekhnika: AllUkr. Sci. Interdep. Mag., 2015; 183: 32-41.
- [19] Al-Janabi H.D.K. Model Of Evolution Of Sub-Channels Scheduling to Improve Quality of Service in WiMAX Network / Haider D.K. Al-Janabi, Hussam D.K. Al-Janabi, A.M. Al-Dulaimi // East European Journal of Advanced Technology. – 2015. – № 2/9 (74). – P. 25-29.
- [20] O.V. Lemeshko Method of presentation integer problem frequency resource allocation in LTE and WiMAX networks as nonlinear programming / OV Lemeshko, AM Al-Dulaimi, HD Al-Janabi // Системи обробки інформації, 2016.